


PCIE-Q670-R20

Full-size PICMG 1.3 CPU card supports LGA 1155 32nm Intel® Core™ i7/i5/i3, Pentium® or Celeron® CPU with Intel® Q67, DDR3, VGA, dual Intel® PCIe GbE, SATA 6Gb/s, PCIe Mini, HD Audio and RoHS



Features

- PICMG 1.3 full-size graphics grade solution
- LGA 1155 Intel® Core™ i7/i5/i3, Pentium® or Celeron® processors supported
- Up to 16 GB 1333 MHz dual-channel DDR3 SDRAM
- Supports dual independent display by VGA
- Supports RAID function via SATA 6Gb/s and SATA 3Gb/s
- TPM v1.2 hardware security provided by the TPM module
- IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Specifications

- ◆ CPU: LGA 1155 socket supports Intel® Core™ i7/i5/i3, Pentium® or Celeron® processor
- ◆ Chipset: Intel® Q67
- ◆ Memory: Two 240-pin 1333/1066 MHz dual-channel unbuffered DDR3 & DDR3L SDRAM DIMMs support up to 16 GB
- ◆ BIOS: UEFI BIOS
- ◆ Graphics Engine: Intel® HD Graphics Gen 6 supports DX10.1 and OpenGL 3.0 Full MPEG2, VC1, AVC Decode
- ◆ Display Output
 - 1 x VGA (up to 2048x1536@75Hz)
- ◆ Ethernet
 - LAN1: Intel® 82583V PCIe controller
 - LAN2: Intel® 82579 PHY with Intel® AMT 7.0 support
- ◆ External I/O Interface
 - 2 x USB 2.0
- ◆ Internal I/O Interface
 - 1 x KB/MS (1x6 pin)
 - 1 x LPT (2x13 pin)
 - 1 x RS-422/485 (1x4 pin, P=2.0)
 - 2 x SATA 6Gb/s (RAID 0/1/5/10 supported)
 - 4 x RS-232 (2x5pin, P=2.54)
 - 4 x SATA 3Gb/s (RAID 0/1/5/10 supported)
 - 4 x USB 2.0 (Golden finger)
 - 6 x USB 2.0 (2x4 pin, P=2.54)
- ◆ Front Panel: 1 x Front panel connector (2x7 pin, power LED, HDD LED, speaker, power button, reset button)
- ◆ Audio: Supports 7,1-channel HD Audio by IEI AC-KIT-892HD-R10 kit
- ◆ TPM: 1 x TPM (2x10 pin)
- ◆ SMBus: 1 x SMBus (1x4 pin)
- ◆ Infrared Interface: 1 x Infrared Interface (1x5 pin)
- ◆ Expansion
 - PCIe signal and PCI signal via golden finger
 - 1 x Full/Half-size PCIe Mini card slot
- ◆ Watchdog Timer: Software programmable supports 1~255 sec. system reset
- ◆ Digital I/O: 8-bit digital I/O (2x5 pin)
- ◆ Fan Connector: 1 x Smart fan (1x4 pin)
- ◆ Power Supply: AT/ATX power supply supported
- ◆ Power Consumption
 - 5V@3.45A, 12V@0.32A, Vcore_12V@5.24A, 3.3V@1.69A, 5VSB@0.17A (3.4GHz Intel® Core™ i7-2600K with two 2 GB 1333 MHz DDR3 memory)
 - ◆ Operating Temperature: -10°C ~ 60°C
 - ◆ Storage Temperature: -20°C ~ 70°C
 - ◆ Operating Humidity: 5% ~ 95%, non-condensing
 - ◆ Dimensions: 338 mm x 126 mm
 - ◆ Weight: GW: 1200g / NW: 420g
 - ◆ CE/FCC compliant

Packing List


1 x PCIE-Q670 single board computer	4 x SATA cable
1 x Dual RS-232 cable	1 x Mini jumper pack
1 x USB cable	1 x QIG

Ordering Information

Part No.	Description
PCIE-Q670-R20	Full-size PICMG 1.3 CPU card supports LGA 1155 32nm Intel® Core™ i7/i5/i3, Pentium® or Celeron® CPU with Intel® Q67, DDR3, VGA, dual Intel® PCIe GbE, SATA 6Gb/s, PCIe Mini, HD Audio and RoHS
19800-000049-RS	LPT flat cable, 240mm, P=2.54
19800-000075-RS	PS/2 KB/MS cable with bracket, 220mm, P=2.0
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32205-003800-300-RS	RS-422/485 cable, 200mm, P=2.0
AC-KIT-892HD-R10	7.1-channel HD Audio kit with Realtek ALC892 supports dual audio streams
CF-115XA-R10	High-performance LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 73W
CF-115XC-R10	LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 45W
CF-115XD-R10	LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 65W
CF-115XE-R10	High-performance LGA 1155/LGA 1156 cooler kit, 95W
CPU-DT-C-G440	Intel® Celeron® G440 processor, LGA 1155, single core 1.6GHz, 1M cache, 35W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i3-2120T	Intel® Core™ i3-2120T processor, LGA 1155, dual core 2.6GHz, 3M cache, 35W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i5-2390T	Intel® Core™ i5-2390T processor, LGA 1155, dual core 2.7GHz, 3M cache, 35W, AMT, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i5-2500T	Intel® Core™ i5-2500T processor, LGA 1155, quad core 2.3GHz, 6M cache, 45W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-P-G630T	Intel® Pentium® G630T processor, LGA 1155, dual core 2.3GHz, 3M cache, 35W, compatible with CF-115XC-R10 CPU cooler
SAIDE-KIT01-R10	SATA to IDE/CF converter board

PCIE-H610

Full-size PICMG 1.3 CPU Card supports 32nm LGA 1155 Intel® Core™ i7/i5/i3, Pentium® or Celeron® CPU with Intel® H61, DDR3, VGA, USB 2.0, SATA 3Gb/s, Dual Realtek PCIe GbE, HD Audio and RoHS



Features

- Full-size PICMG 1.3 graphics grade solution
- LGA 1155 Intel® Core™ i7/i5/i3, Pentium® or Celeron® processor supported
- Dual-channel 1333/1066 MHz DDR3/DDR3L SDRAM supported up to 16 GB
- Intel® HD graphics technology integrates high-performance graphics and media processing
- TPM v1.2 hardware security function supported by TPM module
- IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Specifications

- ◆ CPU: LGA 1155 socket supports Intel® Core™ i7/i5/i3, Pentium® or Celeron® processor
- ◆ Chipset: Intel® H61
- ◆ Memory: Two 240-pin 1333/1066 MHz dual-channel unbuffered DDR3 & DDR3L SDRAM DIMMs support up to 16 GB
- ◆ BIOS: UEFI BIOS
- ◆ Graphics Engine
 - Intel® HD Graphics Gen 6 supports DX10.1 and OpenGL 3.0
 - Full MPEG2, VC1, AVC Decode
- ◆ Display Output
 - 1 x VGA (up to 2048x1536@75Hz)
 - 1 x DVI-D (up to 1920x1200@60Hz) (via header to IO-KIT-001-R20 DVI-D/USB module) (optional)
- ◆ Ethernet
 - LAN1: Realtek RTL8111E PCIe GbE controller with ASF 2.0 support
 - LAN2: Realtek RTL8111E PCIe GbE controller
- ◆ TPM: 1 x TPM (2x10 pin)
- ◆ SMBus: 1 x SMBus (1x4 pin)
- ◆ PC: 1 x PC (1x4 pin)
- ◆ Infrared Interface: 1 x Infrared Interface (1x5 pin)
- ◆ Digital I/O: 8-bit digital I/O (2x5 pin)
- ◆ External I/O Interface: 2 x USB 2.0
- ◆ Audio: Supports by IEI AC-KIT-892HD-R10 audio kit
- ◆ Internal I/O Interface
 - 1 x FDD (2x17 pin)
 - 1 x KB/MS (1x6 pin)
 - 1 x LPT (2x13 pin)
 - 4 x SATA 3Gb/s
 - 1 x RS-422/485 (1x4 pin, P=2.0)
 - 2 x RS-232 (2x5pin, P=2.54)
 - 4 x USB 2.0 (2x4 pin, P=2.54)
 - 4 x USB 2.0 (Golden finger)
- ◆ Front Panel
 - 1 x Front panel (2x7 pin, power LED, HDD LED, speaker, power button, reset button)
- ◆ Expansion: PCIe signal and PCI signal via golden finger
- ◆ Watchdog Timer: Software programmable supports 1~255 sec. system reset
- ◆ Fan Connector: 1 x Smart fan (1x4 pin)
- ◆ Power Supply: 5V/12V, AT/ATX support
- ◆ Power Consumption
 - 5V@4.41A, 12V@0.21A, Vcore_12V@7.72A, 3.3V@1.71A, 5VSB@0.16A (3.4GHz Intel® Core™ i7-2600K with two 2 GB 1333 MHz DDR3 memory)
 - ◆ Operating Temperature: -10°C ~ 60°C
 - ◆ Storage Temperature: -20°C ~ 70°C
 - ◆ Operating Humidity: 5% ~ 95%, non-condensing
 - ◆ Dimensions: 338 mm x 126 mm
 - ◆ Weight: GW: 1200g / NW: 420g
 - ◆ CE/FCC compliant

Packing List

1 x PCIE-H610 single board computer	4 x SATA cable
1 x Dual RS-232 cable	1 x Mini jumper pack
1 x USB cable	1 x QIG

Ordering Information

Part No.	Description
PCIE-H610-R10	Full-size PICMG 1.3 CPU card supports 32nm LGA 1155 Intel® Core™ i7/i5/i3 CPU with Intel® H61, DDR3, VGA, dual Realtek PCIe GbE, USB 2.0, SATA 3Gb/s, HD Audio and RoHS
PCIE-H610-DVI-R10	Full-size PICMG 1.3 CPU card supports 32nm LGA 1155 Intel® Core™ i7/i5/i3 CPU with Intel® H61, DDR3, VGA, DVI-D, dual Realtek PCIe GbE, USB 2.0, SATA 3Gb/s, HD Audio and RoHS
19800-000049-RS	LPT flat cable, 240mm, P=2.54
19800-000075-RS	PS/2 KB/MS cable with bracket, 220mm, P=2.0
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32200-000017-RS	FDD Cable, 520mm, P=2.54
32205-003800-300-RS	RS-422/485 cable, 200mm, P=2.0
AC-KIT-892HD-R10	7.1-channel HD Audio kit with Realtek ALC892 supports dual audio streams
CF-115XA-R10	High performance LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 73W
CF-115XC-R10	LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 45W
CF-115XD-R10	LGA 1155/LGA 1156 cooler kit, 1U chassis compatible, 65W
CF-115XE-R10	High performance LGA 1155/LGA 1156 cooler kit, 95W
CPU-DT-C-G440	Intel® Celeron® G440 processor, LGA 1155, single core 1.6GHz, 1M cache, 35W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i3-2120T	Intel® Core™ i3-2120T processor, LGA 1155, dual core 2.6GHz, 3M cache, 35W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i5-2390T	Intel® Core™ i5-2390T processor, LGA 1155, dual core 2.7GHz, 3M cache, 35W, AMT, compatible with CF-115XC-R10 CPU cooler
CPU-DT-i5-2500T	Intel® Core™ i5-2500T processor, LGA 1155, quad core 2.3GHz, 6M cache, 45W, compatible with CF-115XC-R10 CPU cooler
CPU-DT-P-G630T	Intel® Pentium® G630T processor, LGA 1155, dual core 2.3GHz, 3M cache, 35W, compatible with CF-115XC-R10 CPU cooler
SAIDE-KIT01-R10	SATA to IDE/CF converter board
TPM-IN01-R20	20-pin Infineon TPM module, software management tool, firmware v3.17