

# EB-101-H110



## 产品特性

- ◆ 1\*PCIe x4, 1\*Mini PCIe, 1\*mSATA
- ◆ Intel® H110芯片组
- ◆ 支持双通道DDR4 SODIMM 至 32GB
- ◆ 1\*LVDS, 1\*DVI-I, 1\*HDMI/DP (DP available upon request)
- ◆ 2\*Intel网口, 8\*USB, 4\*串口

## 产品规格

处理器	6/7th Generation Intel® Core™ processors, LGA 1151 socket		扩展槽	1*PCIe x4 (Gen 2), 1*Half-size Mini PCIe (USB/PCIe), 1*Full-size mSATA (USB/SATA)
系统芯片组	Intel® H110 Chipset			
系统内存	2*260-pin SODIMM up to 32GB, Dual Channel DDR4 1866/2133MHz			
BIOS	Insyde SPI 128Mbit		显示	1*DVI-I (DVI-D signal): resolution up to 1920x1200 @ 60Hz 1*LVDS: dual channel, resolution up to 1920x1200 @ 60Hz 1*HDMI/DP(DP available upon request) HDMI: resolution up to 2560x1600 @ 60Hz or 4096x2160 @ 24Hz DP:resolution up to 4096x2304 @ 60Hz
以太网	1*Intel® I211AT PCIe (10/100/1000Mbps) 1*Intel® I219V PCIe (10/100/1000Mbps)			
背部I/O接口	以太网	2*GbE (RJ-45)		
	USB	4*USB 3.0		
	PS/2	1*PS/2		
内部I/O接口	显示	1*DVI-I (DVI-D signal), 1*HDMI*/DP (DP available upon request)	音频	Realtek ALC888S-VD2-GR
	串行端口	3*RS-232 (2.00mm pitch) 1*RS-232/422/485 (RS-232 w/ power) (2.00mm pitch)	温度	工作温度: 0 to 60°C, 存储温度: -40 to 85°C
	USB	4*USB 2.0 (2.00mm pitch)	湿度	工作湿度: 5 to 90% RH, 存储湿度: 5 to 90% RH
	显示	1*LVDS LCD Panel Connector, 1*LCD/Inverter Power		
	音效	1*Audio (Line-out/Mic-in), 1*S/PDIF	尺寸	170mm (6.7")*170mm (6.7")
	SATA	2*SATA 3.0 (up to 6Gb/s)		
DIO	1*8-bit DIO			

## 订货信息

型号	说明
EB-101-H110-XX	Mini-ITX Motherboard supports LGA 1151 Intel® Core™ i7/i5/i3/Pentium, Intel® H110