



### 产品特性

- ◆ 1\*PCIe x16, 1\*M.2 2230 E Key, 1\*M.2 2280 M Key
- ◆ Intel® H310芯片组
- ◆ 支持双通道 DDR4 SODIMM 至 32GB
- ◆ 独立双显: LVDS + VGA, LVDS + DP++, VGA + DP++, DP++ + DP++
- ◆ 2\*Intel网口, 6\*USB, 2\*串口

### 产品规格

处理器	8/9th Generation Intel® Core™ Processors, LGA 1151 Socket		扩展槽	1*PCIe x16 (Gen3) 1*M.2 2280 M Key (PCIe x1 Gen2) (support NVMe) 1*M.2 2230 E Key (USB/PCIe x1 Gen2)
系统芯片组	Intel® H310 Chipset			
系统内存	2*260-pin non-ECC SODIMM up to 32GB, Dual Channel DDR4 2400/2666MHz			
BIOS	AMI SPI 128Mbit		显示	1*LVDS: resolution up to 1920x1200 @ 60Hz 1*VGA: resolution up to 1920x1200 @ 60Hz 2*DP++: resolution up to 4096x2304 @ 60Hz
以太网	1*Intel® I219V PHY (10/100/1000Mbps) 1*Intel® I210AT PCIe (10/100/1000Mbps)			
背部I/O接口	以太网	2*GbE (RJ-45)	音频	Realtek ALC888/887
	USB	4*USB 3.1 Gen1, 2*USB 2.0		
	显示	1*VGA(DB-15), 2*DP++		
	串口	2*RS232(DB-9)		
内部I/O接口	音源	1*Line-in, 1* Line-out, 1*Mic-in	温度	工作温度: -5 to 65°C, 存储温度: -40 to 85°C
	USB	2*USB 2.0(2.00mm pitch)		
	音效	1*Front Audio (2.00mm pitch)	湿度	工作湿度: 5 to 90% RH, 存储湿度: 5 to 90% RH
	SATA	2*SATA 3.0 (up to 6Gb/s)		
	DIO	1*8-bit DIO, 1*DIO Power		
显示	1*LVDS, 1*LCD/Inverter Power	尺寸	170mm (6.7")*170mm (6.7")	

### 订货信息

型号	说明
EB-170-H310-XX	Mini-ITX Motherboard supports LGA 1151 Intel® Core™ i7/i5/i3/Pentium, Intel® H310