

EB-350-Q370



产品特性

- ◆ 2*PCIe x16, 2*PCIe x4
- ◆ Intel® Q370芯片组
- ◆ 支持四通道 DDR4 DIMM 至 128GB
- ◆ 1*HDMI,1*DVI-I(DVI-D signal),1*DP++
- ◆ 2*Intel网口, 12*USB, 4*串口

产品规格

处理器	8/9th Generation Intel® Core™/Pentium®/Celeron® LGA 1151 socket Processors		扩展槽	2*PCIe x16 (Gen3) (1*16 signal or 2*8 signals) 2*PCIe x4(Gen 3) 1*M.2 2230 E key (PCIe*1/USB2.0/intel CNVi support) 1*M.2 2242/2260/2280 M key (PCIe Gen3*4NVMe)
系统芯片组	Intel® Q370 Chipset			
系统内存	4*288-pin DIMM up to 128GB, Dual Channel DDR4 2400/2666MHz(non ECC support)			
BIOS	AMI SPI 128Mbit			
以太网网络	1*Intel® I211AT PCIe (10/100/1000Mbps) 1*Intel® I219LM PCIe(10/100/1000Mbps) with iAMT12.0 (only Corei7/i5 supports iAMT)		显示	1*HDMI: resolution up to 4096x2160@ 24Hz 1*DP++: resolution up to 4096x2106 @ 60Hz 1*DVI-I(DVI-D signal): resolution up to 1920x1200 @ 60Hz
背部I/O接口	以太网网络	2*GbE (RJ-45)		
	串口	1*RS-232/422/485(RS-232 w/power)(DB-9)		
	USB	2*USB 3.1 Gen 2,2*USB 3.1 Gen 1,2*USB 2.0		
	显示	1*DVI-I(DVI-D signal)1*DP++,1*HDMI		
	音源	1*Line-out,1*Mic-in,1*Line-in(opt.,MOQ required)		
内部I/O接口	串行端口	1*RS-232/422/485 (RS-232 w/power) (2.54mm pitch),2*RS-232	温度	工作温度: -5 to 65°C 存储温度: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
	USB	2*USB 3.1 Gen 2,4*USB 2.0(2.54mm pitch) (1*USB 2.0 colay vertical Type A)(opt.,MOQ required)	湿度	工作湿度: 5 to 90% RH, 存储湿度: 5 to 90% RH
	音效	1*Front Audio Header,1*S/PDIF	尺寸	244mm (9.6")*244mm (9.6")
	SATA	6*SATA 3.0 (up to 6Gb/s) RAID 0/1/5/10		
	DIO	1*8-bit DIO		

订货信息

型号	说明
EB-350-Q370-XX	Micro ATX Motherboard supports LGA 1151 Intel® Core™i7/i5/i3/Pentium®/Celeron , Intel® Q370