



产品特性

- ◆ 1*PCIe x16,1*PCIe*4,2*PCI
- ◆ Intel® H420E芯片组
- ◆ 支持双通道 288-pin Non-ECC UDIMM至 64GB
- ◆ 独立双显:VGA + DP++/VGA + HDMI/DP++ + HDMI
- ◆ 2*Intel网口,10*USB, 6*串口

产品规格

处理器	10th Generation Intel® LGA 1200 socket Processors, TDP support up to 125W		扩展槽	1*PCIe x16 (Gen3), 1*PCIe x4(Gen 3), 2*PCI
系统芯片组	Intel® H420E Chipset			
系统内存	2*288-pin Non-ECC UDIMM up to 64GB, Dual Channel DDR4 2400/2666/2933MHz			
BIOS	AMI SPI 256Mbit		显示	1*VGA: resolution up to 1920x1200 @ 60Hz 1*HDMI: resolution up to 4096x2160@ 24Hz 1*DP++: resolution up to 4096x2160 @ 60Hz
以太网	1*Intel® I211AT PCIe (10/100/1000Mbps), 1*Intel® I219LM PHY (10/100/1000Mbps)			
背部I/O接口	以太网	2*GbE (RJ-45)		
	串口	1*RS-232/422/485(RS-232 w/power)(DB-9)		
	USB	2*USB 3.2 Gen 1,2*USB 2.0		
	显示	1*VGA,1*DP++,1*HDMI		
内部I/O接口	PS/2	1*PS/2(mini-DIN-6)	音频	Realtek ALC888
	音源	1*Line-out,1*Mic-in,1*Line-in(opt.,MOQ required)	温度	工作温度: -5 to 65°C 存储温度: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
	串行端口	5*RS-232 (2.54mm pitch) (Up to 9*RS232,MOQ required)		
	USB	2*USB 3.2 Gen 1,2*USB 2.0(2.54mm pitch colay vertical Type A,opt.,MOQ required)	湿度	工作湿度: 5 to 95% RH, 存储湿度: 5 to 95% RH
	音效	1*Front Audio Header,1*S/PDIF	尺寸	244mm (9.6")*244mm (9.6")
SATA	4*SATA 3.0 (up to 6Gb/s)			
DIO	1*16-bit DIO			

订货信息

型号	说明
EB-330-H420-XX	Micro ATX Motherboard supports LGA 1200 Intel® Core™/Pentium®/Celeron Processors i9/i7/i5/i3, Intel® H420